SPECIAL EXECUTIONS - WATERPROOF IP67 PRESSURE CONTROLLERS



电气连接 / ELECTRIC CONNECTION											
接头 Delphi	德驰DT04 Deutsch DT04	德驰DT06 Deutsch DT06	DIUG 按头 DIUG Amn Sunerseal Flying leads Flying le		飞线2根电缆 Flying leads 2 cables	集成 Amp Integrated	M12x1集成 M12x1 integrated				
A B											

可调式压力控制器 PRESSURE CONTROLLER	接头 DELPHI	德驰DT04 DEUTSCH DT04	德驰DT06 DEUTSCH DT06	接头 AMP SUPERSEAL	飞线2根电缆 FLYING LEADS 2 CABLES	飞线3根电缆 FLYING LEADS 3 CABLES	飞线4根电缆 FLYING LEADS 4 CABLES	AMP 集成 AMP INTEGRATED	M12x1集成 M12X1 INTEGRATED
PMN 第9页 Page 09	•	•	•	•	•			•	•
PM250 第13页 Page 13	•	•	•	•		•		•	•
MS 第15页 Page 15	•	•	•	•			•	•	•
PS 第15页 Page 15	•	•	•	•			•	•	•

压力控制器最好在工厂设定。对于不同的配置,请联系我们的销售办事处。

Pressure controllers must be set in factory at first. For different executions please contact our sales office.

Elettrotec保留未经事先通知更改产品技术数据或暂停生产的权利。该压力控制器触点受到强烈冲击或震动时可能会被损坏。用户有责任对我们的产品是否适合特定应用进行测试,例如,材料的兼容性测试。仅在现场试验中得到证实的使用才会是适当的。该样本中的技术信息基于产品开发过程中的测试和经验值的积累,他们可能并不适用于所有情况。

Elettrotec reserves the right to technical data of change to the products or halt production without prior notice. The pressure controller contacts can be damaged when subject to strong shocks or high vibration. It is the responsibility of the user to test the suitability of our products for the particular application, for example, the verification of material compatibility. The use may only be appropriate if proven in field tests. The technical information in this catalogue are based on tests made during product development and based on empirically gathered values. They may not be applicable in all cases.

